



Kółko Ø38 z gumową oponą **Materiał:** kółko - guma, elementy metalowe - stal ocynkowana

Art.	H	S	Hamulec	↓/↑	A x B	M x N x G
#004.500.001	50	18	Nie	40/40	36 x 29	45 x 38 x 2
#004.500.002	50	18	Tak	40/40	36 x 29	45 x 38 x 2



Kółko Ø38 z oponą z PCV **Materiał:** kółko - PCV, elementy metalowe - stal ocynkowana

Art.	H	S	Hamulec	↓/↑	A x B	M x N x G
#004.500.003	50	18	Nie	40/40	36 x 29	45 x 38 x 2
#004.500.004	50	18	Tak	40/40	36 x 29	45 x 38 x 2



Kółko Ø50 z gumową oponą **Materiał:** osłona koła i trzpień - czarny nylon

Art.	H	S	Hamulec	↓/↑	A x B	M x N x G
#08.04.099	65	45	Nie	50/30	32 x 32	42 x 42 x 2



Rekomendowane do twardych powierzchni

Kółko Ø50 **Materiał:** kółko - szary poliuretan, rdzeń kółka - czarny polipropylen, elementy metalowe - stal ocynkowana

Art.	H	S	Hamulec	↓/↑	A x B	M x N x G
#08.12.230	65	18	Nie	60/35	32 x 32	42 x 42 x 1,5
#08.12.231	65	18	Tak	60/35	32 x 32	42 x 42 x 1,5



Rekomendowane do twardych powierzchni

Kółko Ø50 z gumową oponą **Materiał:** kółko - guma, elementy metalowe - stal ocynkowana

Art.	H	S	Hamulec	↓/↑	A x B	M x N x G
#004.500.010	72	18	Nie	50/50	37 x 37	50 x 50 x 1,5
#004.500.011	72	18	Tak	50/50	37 x 37	50 x 50 x 1,5



Kółko Ø65 z gumową oponą **Materiał:** osłona koła i trzpień - czarny plastik

Art.	H	S	Hamulec	↓/↑	A x B	M x N x G
#08.04.200	77	45	Nie	80/50	32 x 32	42 x 42 x 2
#08.04.201	77	45	Tak	80/50	32 x 32	42 x 42 x 2



Rekomendowane do twardych powierzchni

Kółko Ø75 **Materiał:** kółko - szary poliuretan, rdzeń kółka - czarny polipropylen, elementy metalowe - stal ocynkowana

Art.	H	S	Hamulec	↓/↑	A x B	M x N x G
#08.12.232	97	24	Nie	100/60	46 x 46	60 x 60 x 2,5
#08.12.233	97	24	Tak	100/60	46 x 46	60 x 60 x 2,5



Rekomendowane do twardych powierzchni

Kółko Ø76 **Materiał:** kółko - szary plastik, płyta metalowa - stal ocynkowana

Art.	H	S	Hamulec	↓/↑	A x B	M x N x G
#08.12.400	100	47	Nie	50/25	32 x 32	42 x 42 x 2
#08.12.405	100	47	Tak	50/25	32 x 32	42 x 42 x 2

